




New Product

ETA
1/3/2016

Cheap stereoscopic downlights


A downlight that everyone can afford it

E6 series of downlights with hexagonal back cover presents a unique three-dimensional nature of the product. The lighting design from architectural aesthetics still full consideration and ceiling decoration of overall coordination, to ensure the product itself decorative. Meanwhile, more Family brought ceiling decoration unified solution.




Artistic temperament

Pure white casing, the elegant presentation to the extreme. Perfect match with the ceiling, so that the whole home atmosphere full of art.




Light stability

LED fast response, completely eliminating the traditional high pressure sodium lamp starter long process shortcomings can be avoided. CFL on and off frequently cause filament black, quickly damaged.



Thermal stability

Aluminum housing built to ensure the cooling, excellent thermal management, to ensure long-term stable LED light tube, effectively control lumen attenuation problems.



Featured materials

Using V-0 fire rating PBT housing material, with anti-yellowing and never change the function.



High security

Adding main voltage through the terminal and safe lock design, ease of installation, no security risks.



Easy to install

Integrated drive device, immediate plug and immediate use, simple wire connection



新品

ETA
1/3/2016



3"



BarCode	001857	001864	001871	001888
Power	5W	5W	7W	7W
CCT	4000K	6000K	4000K	6000K
Brightness	420lumen	440lumen	570lumen	580lumen
Incandescent Lamp Power	42W	44W	57W	58W
MEAS	D95*H56mm			
Cutout size	Φ68-80mm			

CRI : > 80Ra

PF : > 0.9

Life span : 30000Hours

Beam angle : 90°

Protection : IP44

EEI : A+

4"



BarCode	001895	001901
Power	10W	10W
CCT	4000K	6000K
Brightness	900lumen	920lumen
Incandescent Lamp Power	90W	92W
MEAS	D115*H57mm	
Cutout size	Φ90-102mm	

CRI : > 80Ra

PF : > 0.9

Life span : 30000Hours

Beam angle : 90°

Protection : IP44

EEI : A+



5"



BarCode	001918	001925
Power	15W	15W
CCT	4000K	6000K
Brightness	1300lumen	1320lumen
Incandescent Lamp Power	130W	132W
MEAS	D145*H62mm	
Cutout size	Φ120-130mm	

CRI : > 80Ra

PF : > 0.9

Life span : 30000Hours

Beam angle : 90°

Protection : IP44

EEI : A+

8"



BarCode	001932	001949
Power	25W	25W
CCT	4000K	6000K
Brightness	2250lumen	2300lumen
Incandescent Lamp Power	225W	230W
MEAS	D245*H75mm	
Cutout size	Φ195-210mm	

CRI : > 80Ra

PF : > 0.9

Life span : 30000Hours

Beam angle : 90°

Protection : IP44

EEI : A+